

RAM

09-2010
2500/3500 4WD

09-2010
POWERWAGON 4WD

Fits up to 37-in. tires

Maintains proper driveshaft angles - minimizing vibrations

New forged pitman arm

New heavy-duty tubular-style front links

Aligns to OE specifications

Rear leaf spring blocks

Allows for reuse of the stock wheels

CAD designed components ensure a precise fit

This suspension system was developed using a 37 x 12.50 x R17
Shocks sold separately.



Available in black finish only
Coil springs and shocks sold separately

RS6585B



RAM

**09-2010
2500/3500 4WD**
**09-2010
POWERWAGON 4WD**
Fits up to 37-in. tires

Maintains proper driveshaft angles - minimizing vibrations

- New forged pitman arm**
- New heavy-duty tubular-style front links
- Aligns to OE specifications
- Rear leaf spring blocks
- Allows for reuse of the stock wheels
- CAD designed components ensure a precise fit

This suspension system was developed using a 37 x 12.50 x R17
Shocks sold separately.



Available in black finish only
Coil springs and shocks sold separately

YEAR	MODEL	HEIGHT (in.)		FRONT SPRING	REAR KIT	PRIMARY SUSPENSION SYSTEM	SHOCK ABSORBERS		DEVELOPED TIRE SIZE
		FRONT	REAR				FRONT	REAR	
09-2010	4WD Ram 2500 Mega Cab Diesel	4.00	2.50	RS80121B	RS747 ²²⁰	RS6585B	RS999317 ^{XL} RS5317 ^{R5}	RS999056 ^{XL} RS5056 ^{R5}	37 x 12.50 x R17
09-2010	4WD Ram 2500 Mega Cab - Exc. Diesel	4.00	2.50	RS80122B	RS748 ²²⁰	RS6585B ¹⁵⁴	RS999317 ^{XL} RS5317 ^{R5}	RS999056 ^{XL} RS5056 ^{R5}	37 x 12.50 x R17
09-2010	4WD Ram 2500 Diesel - Inc. Reg & Ext. Cab	4.00	2.50	RS80121B	RS747 ²²⁰	RS6585B	RS999317 ^{XL} RS5317 ^{R5}	RS999056 ^{XL} RS5056 ^{R5}	37 x 12.50 x R17
09-2010	4WD Ram 2500 Reg Cab, Ext Cab - Exc. Diesel	4.00	2.50	RS80120B	RS748 ²²⁰	RS6585B ¹⁵⁴	RS999317 ^{XL} RS5317 ^{R5}	RS999056 ^{XL} RS5056 ^{R5}	37 x 12.50 x R17
09-2010	4WD Ram 2500 Power Wagon 5.7L Hemi	4.00	2.50	Inc.	Inc.	RS6584B ¹⁵⁴	RS999317 ^{XL} RS5317 ^{R5}	RS999056 ^{XL} RS5056 ^{R5}	37 x 12.50 x R17
09-2010	4WD Ram 3500 Mega Cab Diesel - Exc. Dual rear wheels	4.00	2.50	RS80121B	RS747 ²²⁰	RS6585B	RS999317 ^{XL} RS5317 ^{R5}	RS999056 ^{XL} RS5056 ^{R5}	37 x 12.50 x R17
09-2010	4WD Ram 3500 Mega Cab - Exc. Diesel and dual rear wheels	4.00	2.50	RS80120B	RS748 ²²⁰	RS6585B ¹⁵⁴	RS999317 ^{XL} RS5317 ^{R5}	RS999056 ^{XL} RS5056 ^{R5}	37 x 12.50 x R17
09-2010	4WD Ram 3500 Diesel - Exc. Dual rear wheels	4.00	2.50	RS80121B	RS747 ²²⁰	RS6585B	RS999317 ^{XL} RS5317 ^{R5}	RS999056 ^{XL} RS5056 ^{R5}	37 x 12.50 x R17
09-2010	4WD Ram 3500 - Exc. Diesel and dual rear wheels	4.00	2.50	RS80120B	RS748 ²²⁰	RS6585B ¹⁵⁴	RS999317 ^{XL} RS5317 ^{R5}	RS999056 ^{XL} RS5056 ^{R5}	37 x 12.50 x R17

²²⁰ Carrier bearing spacer P/N RS6608 is required on vehicles equipped with rear drive shaft carrier bearing. Minimal driveline vibration may be present in 4WD.
¹⁵⁴ Exhaust modification is required, check local laws regarding exhaust modification prior to installation.
Shocks sold separately. XL designates RS9000XL™ shock absorber. R5 designates RS5000™ shock absorber.